

# 25 CAL/CM<sup>2</sup> PRISM SHIELD PLUS LIFT FRONT HOOD

## Technical Datasheet

Honeywell Salisbury's LFH25POR-PP PrismShield Plus face shield is intended to provide protection against the heat and blast release in an arc flash event rated 25 cal/cm<sup>2</sup> or lower. The face shield and shroud parts are considered pieces of the full unit and both must be worn in order to provide full protection.

### PART NUMBER

- LFH25POR-PP: 25 cal/cm<sup>2</sup> premium lift front hood face shield



### STANDARDS INFORMATION

AGENCY SPECIFICATION	
ASTM F2178	Standard test method for determining the arc rating and standard specification for eye or face protective products.
ANSI Z87.1	Occupational and educational personal eye and face protection devices.
NFPA 70E	American standard for electrical safety in the workplace
ASTM F1506	Standard Performance Specification for Flame Resistant and Electric Arc Rated Protective Clothing Worn by Workers Exposed to Flames and Electric Arcs
CSA Z462	Canadian standard for electrical safety in the workplace

## 25 cal/cm<sup>2</sup> PrismShield Plus Technical Specifications

### MATERIALS INFORMATION

PHYSICAL SPECIFICATIONS	
Viewing area	130 in <sup>2</sup>
ATPV	25 cal/cm <sup>2</sup>
Total weight	2.5 lbs (1.16 kg)
Lens Dimensions	13" Height X 22 1/2" Width
Flash light attachment slots	2
Lens technology	PrismShield Plus
Lens color	Bronze tinted (appears clear)
Lens material	Polycarbonate
Lens speciality coating	Anti-fog, Anti-scratch
Shroud material	Aramid blend
Shroud material weight	5.3 oz/yd <sup>2</sup> over 5.3 oz/yd <sup>2</sup>

### ACCESSORIES & SPARE PARTS

ACCESSORY & SPARE PART ORDERING INFORMATION	
PART NUMBER	ITEM DESCRIPTION
LFH40FSA-PP	40cal/cm <sup>2</sup> Replacement lens for lift-front hood
SHRD-25POR-PP	Replacement shroud for LFH25POR-PP
N10R030000	Replacement N10 hard hat in orange
FLKIT	Attachable task light kit
AS BAG	Face Shield storage bag (21" L, 19" W, 14" H)
SK BAGR	Large Storage Bag (24" L, 20" W, 15" H)
SKBACKPACK	Reinforced specialty backpack (14" L, 8" W, 18" H)

#### Honeywell Salisbury

P.O. Box 70729

North Charleston SC 29415

Phone within US: 877-406-4501

Phone outside US: 630-343-3800

Email (US/CAN): [cssd@honeywell.com](mailto:cssd@honeywell.com)

Email (INTL): [customerservicesalisburyintl@honeywell.com](mailto:customerservicesalisburyintl@honeywell.com)

Email: [salisburyorders@honeywell.com](mailto:salisburyorders@honeywell.com)

**Honeywell**  
**SALISBURY**